















## Hull Zinc Anodes

TYPE		LENGTH mm	WIDTH mm	DEPTH mm	NET WEIGHT Kg	GROSS WEIGHT Kg
<a href="#">CZ 1</a>		110	80	25	1.03	1.10
<a href="#">CZ 2</a>		210	75	35	2.15	2.50
<a href="#">CZ 3</a>		160	83	40	3.10	3.40
<a href="#">CZ 5</a>		300	75	30	4.30	4.70
<a href="#">CZ 7</a>		260	130	50	6.70	7.10
<a href="#">CZ 11</a>		310	150	60	10.90	11.40
<a href="#">CZ 13</a>		530	100	50	13.20	13.90
<a href="#">CZ 16</a>		440	110	65	15.40	16.10
<a href="#">CZ 21</a>		580	115	50	20.80	21.70
<a href="#">CZ 25</a>		670	140	50	24.00	25.00
<a href="#">CZ 8</a>		305	155	30	8.10	8.60
<a href="#">CZ 12</a>		310	160	45	12.40	12.90
<a href="#">CPS 4</a>		305	80	40	3.80	4.30
<a href="#">CPS 7</a>		445	100	45	6.50	7.30

SPECIFICATION	U.S.MIL. A 18001 K			
Pb	0.006% max.	Efficiency:	95%	
Fe	0.005% max.			
Cd	0.025% - 0.07%		Potential:	1.05 volt Ag/Ag Cl Ref. Cell
Cu	0.005% max.			
Al	0.1% - 0.5%			
Zn	99.314% min.		Capacity - Amp/Hour	780 per Kg