















Hull Zinc Anodes

TYPE		LENGTH mm	WIDTH mm	DEPTH mm	NET WEIGHT Kg	GROSS WEIGHT Kg
CZ 1		115	80	30	1.03	1.10
CZ 2		228	76	35	2.15	2.50
CZ 3		175	85	40	3.10	3.40
CZ 5		300	77	32	4.30	4.70
CZ 7		280	130	55	6.70	7.10
CZ 11		340	150	60	10.90	11.40
CZ 13		530	100	50	13.20	13.90
CZ 16		460	100	65	15.40	16.10
CZ 21		610	110	50	20.80	21.70
CZ 25		690	135	50	24.00	25.00
CZ 8		305	155	30	8.10	8.60
CZ 12		310	160	45	12.40	12.90
CPS 4		305	80	40	3.80	4.30
CPS 7		445	100	45	6.50	7.30

SPECIFICATION	U.S.MIL. A 18001 K	
Pb	0.006% max.	Efficiency: 95%
Fe	0.005% max.	
Cd	0.025% - 0.07%	Potential: 1.05 volt Ag/Ag Cl Ref. Cell
Cu	0.005% max.	
Al	0.1% - 0.5%	Capacity - Amp/Hour 780 per Kg
Zn	99.314% min.	