



SYMBOL OF QUALITY
IN SACRIFICIAL ANODES FOR CORROSION CONTROL

ESTALEIROS DA MITRENA 2910-738 SETÚBAL
Telef. 265 719 116 - 265 719 117 - 265 799 385
Fax: 265 719 113 - 265 729 015

CATHODIC PROTECTION DEPARTMENT

Zinc Anodes for Coolers

TYPE		DIAMETER mm	LENGTH mm	WIDTH mm	DEPTH mm	UNIT WEIGHT Kg
V 15		15	380	-	-	0,500
V 20		20	380	-	-	1,000
V 25		25	380	-	-	1,400
V 30		30	380	-	-	2,000
V 35		35	380	-	-	2,700
V 50		50	380	-	-	5,400
V 60		60	380	-	-	7,700
V 75		75	380	-	-	12,100
V 100		100	380	-	-	22,000
C 300		-	300	150	25	7,500
R 80		80 / 12	-	-	10	0,330
R 100		100 / 14	-	-	20	1,000
R 120		120 / 15	-	-	15	1,100
R 180		180 / 24	-	-	20	3,400

SPECIFICATION	U.S.MIL. A 18001 K		
Pb	0.006% max.	Efficiency:	95%
Fe	0.005% max.		
Cd	0.025% - 0.07%	Potential:	- 1.05 volt Ag/Ag Cl Ref. Cell
Cu	0.005% max.		
Al	0.1% - 0.5%	Capacity - Amp/Hour	780 per Kg
Zn	99.314% min.		